


BARIX

THE VOICE OF SIMPLICITY

ANNUNCIKOM 1000

Professional Intercom / Paging device with supervised contact closures and relay outputs, 48V capable



The Annuncikom 1000 is a professional Audio over IP device. With balanced audio and supervised I/O, it is ideal to serve as a gateway between IP Paging, VoIP and Intercom systems.

Supporting both high quality music (MP3) as well as voice codecs (G.711 and G.722*) and a large number of protocols (including shoutcast, SIP etc), the device can be used for both surveillance as well as VoIP applications.

Applications

- Automatic Announcement Systems
- VHF Radio Controller and interface to IP
- Voice Evacuation Systems
- Microphone Encoder for IP Audio Surveillance
- Paging and Audio Distribution with Amplifier control and monitoring
- Live IP Audio Encoder for Streaming Applications
- Generic, bidirectional full-duplex VoIP module for Paging and Intercom applications
- SIP and IP Paging Zone Device

Features

- MP3, G.711, G.722*, PCM Encoding
- MP3, G.711, G.722*, PCM Decoding
- Audio Level Supervision with SNMP Trap generation
- IP Streaming via TCP, UDP, RTP, Multicast
- Microphone Input
- Balanced Line Level Input (2)
- Balanced Line Level Output (2)
- Relay Output (8+1)
- Supervised Contact Closure Input (8)
- RS-232 Serial Port (1)
- RS-485 Serial Port (1)
- Supply Voltage (24-48VDC)
- Battery Backup Supply Input

* Hardware revision 2 only

Technical Specifications

Audio formats

Format	Encode	Decode
PCM	y	y
G.711	y	y
G.722*	y	y
MP3	VBR, CBR*	VBR, CBR*

Discrete Interfaces

- 8 supervised Inputs, 8 Relays (dry contacts)
- 1 Fault Relay output

Audio Interfaces

Mic In (Balanced, Phantom power) or Balanced
Balanced Stereo Line In, 18 kOhm impedance

- Input level software controllable
- Clippinglevel 3.5 dBu, 3.28 Vpp
- Frequency response (-3 dBFS) 20 .. 17000 Hz **
- Signal to Noise Ratio 88 dB, THD (-3 dBFS) < 0.1 %
- Stereo crosstalk -87 dB

Balanced Stereo Line Out, 40 .. 60 Ohm impedance

- Output level software controllable
- Full scale output voltage 5.9 dBu, 4.33 Vpp
- Frequency response (-3 dBFS) 15 .. 21000 Hz **
- Signal to Noise Ratio 92 dB, THD (-3 dBFS) < 0.1 %
- Stereo crosstalk -66 dB

Serial Interfaces

- RS-232 DSub 9 pin male, 300..115200 Baud,
- RS-485 screw terminal block, 300..115200 Baud

Control Interfaces

- web server for control and configuration

Network Interface

- RJ45 10/100 Mbit Ethernet (Auto), TCP/IP, UDP, RTP, SIP, DHCP, SNMP, AutoIP, SonicIP, IPzator

Misc

- Ten status LEDs, reset/factory default button,
- Internal temperature sensor

Power inputs

- Two independent, level supervised inputs
- 24 to 48 VDC $\pm 20\%$ (pos. or neg.), 8 Watt max.

Case:

- Aluminum, 745 g, 8.5" x 1.5" x 4.92"
216 mm x 38 mm x 125 mm

MTBF

- Min. 300 000h acc. to MIL217F at 25°C ambient temperature

* Hardware revision 2 only

** depends on used codec, best results @48KHz PCM

Environmental

Operating Environment

-0 to +40°C / 32 to 104°F

Storage Conditions

0 to +70°C / 32 to 158°F,

both 0 - 70% relative humidity, non-condensing

Certifications/compliant with

FCC A, CE A, RoHS compliant (lead free)

Ordering Information

2007.9076 Annunicom 1000 INTL

For commercial related questions (distributors contacts, price list, business opportunities) please contact

sales@barix.com

For technical inquiries (problem reports, request for documentation, etc) please contact

support@barix.com

Barix AG – Seefeldstrasse 303 – CH-8008 Zurich – info@barix.com – www.barix.com
Phone: +41 43 43322 11 – Fax: +41 44 2742849



© Barix AG 2013, all rights reserved. All information is subject to change without notice.

All mentioned trademarks belong to their respective owners and are used for reference only. Product sheet V3.0